

# KKRWW33

## Specification sheet


Outdoor

Indoor/Outdoor | Surface


# KKDÖ ITALY

24V DC | L70 B10 > 50000h | CE |  | RoHS Compliant | LM79 Tested | LM80 Tested | TM-30 Results

<b>Dimension</b>	H26.1mm x W33mm
<b>LED/m</b>	24
<b>Cover/Optics</b>	20° / 30° / 45° / 20°x40°
<b>CCT</b>	2700K / 3000K / 4000K / 5000K / 5700K
<b>Bin</b>	3-Step MacAdam Ellipse
<b>CRI</b>	90
<b>Lifetime</b>	50,000 hours @ 25°C
<b>Operating Temp.</b>	Ta = -40 to 55°C
<b>IP Rating</b>	IP66
<b>IK Rating</b>	IK06
<b>Finish</b>	Black / White / Custom
<b>Mounting</b>	T-Adjustable Bracket
<b>Accessory</b>	Anti-glare Louvre
<b>Power feed</b>	2 Core Cable with Male/Female Connector (2x1mm <sup>2</sup> Cable Power IN/OUT)
<b>Control(Integrated)</b>	0-10V / 1-10V / DMX / DALI
<b>Certification</b>	CE
<b>Warranty</b>	3 Years
<b>Weight</b>	1.2kg



Grille Louvre



**PRODUCT MODEL** @ 3000K

24 W/m 2160lm/m

### POWER DATA

**Supply voltage** 24V DC

### LENGTH AVAILABILITY

Length Code	Fixture Length (mm)
m0300	300
m0500	500
m1000	1000

