



ONDA-AURORA

NS230&NS157


Specification sheet

Indoor | Outdoor




L70 B10 > 50000h	CE	III	RoHS Compliant	LM79 Tested	LM80 Tested	TM-30 Results
---------------------	----	-----	-------------------	----------------	----------------	------------------

Dimension	H16mm x W16mm x L5000mm (Max)
PCB Increment	Free-cutting to be any length
LED/m	120
Chip	SMD 2835
Cover/Optics	120°
Bend type	Side bend / Top bend
CCT	2700K / 3000K / 3500K / 4000K/5000K/6000K
Bin	3-Step MacAdam Ellipse
CRI	90
TM 30-15 R _q	99
TM 30-15 R _f	91
Lifetime	50,000 hours @ 25°C
Operating Temp.	Ta = -20 to 45°C (Tc≤65°C)
IP Rating	IP67/IP68
IK Rating	IK08
Mounting	Aluminum channel / Clip / Bendable Bracket
Power feed	Tail Feed / Side Feed / Bottom Feed
Control	0-10V / 1-10V / DMX / DALI
Certification	CE , UL, RoHS
Warranty	3 years
Weight	N.W. 1.6kg
Max run	5000mm




PRODUCT DATA @ 4000K

Bend Type	Side Bend (NS230)	Top Bend (NS157)
Power Consumption	14W/m	14W/m
Supply voltage	24V DC	24V DC
Lumen/m	910lm/m	1040lm/m
Lumen/W	65lm/W	74lm/W



NS157



NS230

PERFORMANCE DATA @4000K

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14
98	97	96	96	98	92	90	85	70	97	99	81	99	99

DIMENSIONS VARY BY CABLE EXIT TYPE


Side cable exit



Tail cable exit (Single)



Bottom cable exit



Tail cable exit (Double)




MOUNTING ACCESSORIES

Note: Accessories are to be ordered separately with corresponding code shown below.




Steel clip


- Allow 6 per metre



Bendable Bracket



Aluminum Channel



Plastic Clip

